

**MULTI-STRIPAX PV****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- For flexible and solid conductors with special insulating materials
- High-quality stripping for industrial applications (complies with aircraft industry requirements)
- Specially shaped blades enable stripping of special types of insulation and conductor configurations
- Stripping length adjustable via end stop
- Very versatile thanks to interchangeable stripping units
- Stripping results reproduced accurately over and over again
- No damage to the conductor
- A long-lasting, reliable tool thanks to its sturdy design
- Integrated cutting function

**General ordering data**

|            |                                  |
|------------|----------------------------------|
| Version    | Photovoltaics, Plug-in connector |
| Order No.  | <a href="#">1190490000</a>       |
| Type       | MULTI-STRIPAX PV                 |
| GTIN (EAN) | 4032248973262                    |
| Qty.       | 1 pc(s).                         |

Creation date August 26, 2021 9:20:44 AM CEST

Catalogue status 20.08.2021 / We reserve the right to make technical changes.

**MULTI-STRIPAX PV****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|        |        |                 |            |
|--------|--------|-----------------|------------|
| Depth  | 40 mm  | Depth (inches)  | 1.575 inch |
| Height | 85 mm  | Height (inches) | 3.346 inch |
| Width  | 250 mm | Width (inches)  | 9.842 inch |
| Weight | 250 g  | Net weight      | 548 g      |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Technical data**

|                        |                    |
|------------------------|--------------------|
| Description of article | Wire stripper unit |
|------------------------|--------------------|

**Stripping tools**

|                               |  |  |                     |
|-------------------------------|--|--|---------------------|
| Cable type                    | Photovoltaic cables and similar earthing cables and short-circuit-proof cables | Conductor cross-section (cutting capacity) | 6 mm <sup>2</sup>   |
| Conductor cross-section, max. | 6 mm <sup>2</sup>  | Conductor cross-section, min.              | 2.5 mm <sup>2</sup> |
| Stripping length, min.        | 2 mm   |  |                     |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002109    | ETIM 7.0    | EC002109    |
| ETIM 8.0    | EC002109    | ECLASS 9.0  | 21-04-37-06 |
| ECLASS 9.1  | 21-04-37-06 | ECLASS 10.0 | 21-04-37-06 |
| ECLASS 11.0 | 21-04-37-06 |             |             |

**Approvals**

Approvals

**Downloads**

|                    |  |
|--------------------|--|
| User Documentation | <a href="#">Manual</a>                   |
| Catalogues         | <a href="#">Catalogues in PDF-format</a> |
| Brochures          |  |